

## BARE COB LED STRIP LIGHTS

**Input Voltage:** DC 12V  
**Forward Current:** 0.83A per 1m (512 pcs LED Strip)  
**Power Dissipation:** 10W per 1m (512 pcs LED Strip)  
**Non Water-Proof, IP20:** 2 - Protected against solid objects up to 12mm<sup>3</sup>  
 0 - No protection against liquids

Excellent uniformity of brightness. Long life span LED lights, 30,000 to 50,000 hours.  
 Adhesive back, peel & stick. Ideal for sign letters and channel letters, concealed lights, room lighting

Part Number	Length [m] / LED [PCS]	Emitted Color	Dominant Wavelength [nm]	Color Temperature (CCT) [K]	Luminous Flux [lm/m]	View Angle
55-7630B-0	0.5 / 256	Blue	455 - 470	n/a	380 - 400	180
55-7630G-0		Green	510 - 525	n/a	900 - 1000	
55-7630R-0		Red	620 - 630	n/a	230 - 250	
55-7630W-0		White	n/a	6000 - 7000	1100 - 1200	
55-7630WW-0		Warm White	n/a	3000 - 3500	900 - 1000	
55-7660B-0	1 / 512	Blue	455 - 470	n/a	380 - 400	
55-7660G-0		Green	510 - 525	n/a	900 - 1000	
55-7660R-0		Red	620 - 630	n/a	230 - 250	
55-7660W-0		White	n/a	6000 - 7000	1100 - 1200	
55-7660WW-0		Warm White	n/a	3000 - 3500	900 - 1000	
55-76300B-0	5 / 2560	Blue	455 - 470	n/a	380 - 400	
55-76300G-0		Green	510 - 525	n/a	900 - 1000	
55-76300R-0		Red	620 - 630	n/a	230 - 250	
55-76300W-0		White	n/a	6000 - 7000	1100 - 1200	
55-76300WW-0		Warm White	n/a	3000 - 3500	900 - 1000	

55-76300R-0



55-76300G-0



55-76300B-0



55-76300W-0



55-76300WW-0



55-76COBA-0



8mm Snap-On LED Strip Joiner

55-76COBB-0



8mm Snap-On LED Strip Connector



55-76COBC-0

8mm Snap-On LED Strip Joiner


**Get Connected**  
quality electronic components

## SILICONE SLEEVE COB LED STRIP LIGHTS

**Input Voltage:** DC 12V  
**Forward Current:** 0.83A per 1m (512 pcs LED Strip)  
**Power Dissipation:** 10W per 1m (512 pcs LED Strip)  
**Waterproof IP67:** 6 - Totally protected against dust  
 7 - Protected against the effect of immersion between 15cm and 1m  
**Excellent uniformity of brightness. Long life span LED lights, 30,000 to 50,000 hours.**  
**Adhesive back, peel & stick.**

Part Number	Length [m] / LED [PCS]	Emitted Color	Dominant Wavelength [nm]	Color Temperature (CCT) [K]	Luminous Flux [lm/m]	View Angle
55-7730B-0	0.5 / 256	Blue	455 - 470	n/a	380 - 400	180
55-7730G-0		Green	510 - 525	n/a	900 - 1000	
55-7730R-0		Red	620 - 630	n/a	230 - 250	
55-7730W-0		White	n/a	6000 - 7000	1100 - 1200	
55-7730WW-0		Warm White	n/a	3000 - 3500	900 - 1000	
55-7760B-0	1 / 512	Blue	455 - 470	n/a	380 - 400	
55-7760G-0		Green	510 - 525	n/a	900 - 1000	
55-7760R-0		Red	620 - 630	n/a	230 - 250	
55-7760W-0		White	n/a	6000 - 7000	1100 - 1200	
55-7760WW-0		Warm White	n/a	3000 - 3500	900 - 1000	
55-77300B-0	5 / 2560	Blue	455 - 470	n/a	380 - 400	
55-77300G-0		Green	510 - 525	n/a	900 - 1000	
55-77300R-0		Red	620 - 630	n/a	230 - 250	
55-77300W-0		White	n/a	6000 - 7000	1100 - 1200	
55-77300WW-0		Warm White	n/a	3000 - 3500	900 - 1000	


55-77300R-0



55-77300G-0



55-77300B-0



55-77300W-0



55-77300WW-0



55-76COBA-0



8mm Snap-On LED Strip Joiner

55-76COBB-0



8mm Snap-On LED Strip Connector



55-76COBC-0

8mm Snap-On LED Strip Joiner

Get  
Connected  
quality electronic components

